

Sub B4
A
1. (Amended) A saw blade carry case, comprising:

a front member having at least one crossbar extending across said front member;
a rear member having at least one crossbar extending across said rear member;
a spindle extending between said front and rear members removably received by a receptacle on at least one of said front and rear members;
at least one handle attached to one of said front and rear members;
whereby said front and rear members together form a frame body, said front and rear members each being larger than the diameter of at least one circular saw blade to be placed within said saw blade carry case and to be retained by said spindle, said at least one circular saw blade being viewable at least in part through said frame body, and whereby said carry case may be adjusted so that said spindle may accommodate a varying number of blades.

Sub B6
A 2
24. (Amended) A saw blade carry case comprising a wire frame, said frame comprising:

a front circular member having an upper crossbar and a central crossbar;
a rear circular member having an upper crossbar and a central crossbar;
a panel suitable for displaying an advertisement attached with a lower portion of one of said front and rear members;
a threaded spindle having a first end attached to one of said front and rear members and a second end to removably receive the other of said front and rear members, said spindle extending from the center of one of said members to the center of the other of said members;
a threaded receptacle located on one of said front and rear members to receive said second end of said spindle;
a handle attached to one of said front and rear members;
whereby said front and rear members together form a frame body and wherein said front and rear members are parallel.